

**TODD  
SYSTEMS****ADJUSTABLE STEPDOWN ISOLATION TRANSFORMERS**

FULLY RATED FOR CONTINUOUS USE

DESIGNED AND MADE IN THE USA

OVER 40 YEARS AS THE INDUSTRY LEADER

- U.L. LISTED COMPONENTS
- FULLY RATED AT 50 OR 60 Hz

- CLEARLY MARKED ELECTRICAL RATINGS
- BLUE BAKED ENAMEL FINISH

**AMERICAN STYLE 220V  
GROUNDING PLUG****210/230/250 VOLTS INPUT** → **115 VOLTS OUTPUT****50 → 1000 VA ISOLATION**  
ELECTROSTATIC SHIELD CONNECTED TO CORE

CATALOG NUMBER	MAX.VA (WATTS)	NOMINAL AMPS	HIPOT TEST VOLTS	WEIGHT LBS.	DIMENSIONS				
					H	W	D	MW	MD
LI-50-3G	50	0.44	2000	3	3 1/2	2 7/8	3 7/8	2 1/4	2 1/2
LI-100-3G	100	0.87	2000	4 1/2	3 1/2	2 7/8	4 3/8	2 1/4	3
LI-250-3G	250	2.17	2000	11 1/2	4 5/8	3 7/8	5 1/8	3	4
LI-500-3G	500	4.35	2000	19	6	4 3/8	5 7/8	3 7/16	4 1/8
LI-1000-3G	1000	8.70	2000	34	6	4 3/8	8 1/8	3 7/16	6 3/8

IN STOCK



PLUG



RECEPTACLE



Provides isolation of power line from ground and is effective in removing hash and line noise for sensitive equipment, e.g. lab instruments, audio equipment, etc.

- 6 FOOT 3 WIRE POWER CORD WITH GROUNDING U.S. TANDEM 220V PLUG
- BUILT-IN U.S. 3 WIRE GROUNDING RECEPTACLE
- SWITCH FOR INPUT VOLTAGE SELECTION

**EUROPEAN STYLE  
SCHUKO PLUG****210/230/250 VOLTS INPUT** → **115 VOLTS OUTPUT****50 → 1000 VA ISOLATION**  
ELECTROSTATIC SHIELD CONNECTED TO CORE

CATALOG NUMBER	MAX.VA (WATTS)	NOMINAL AMPS	HIPOT TEST VOLTS	WEIGHT LBS.	DIMENSIONS				
					H	W	D	MW	MD
LI-50-3SC	50	0.44	2000	3	3 1/2	2 7/8	3 7/8	2 1/4	2 1/2
LI-100-3SC	100	0.87	2000	4 1/2	3 1/2	2 7/8	4 3/8	2 1/4	3
LI-250-3SC	250	2.17	2000	11 1/2	4 5/8	3 7/8	5 1/8	3	4
LI-500-3SC	500	4.35	2000	19	6	4 3/8	5 7/8	3 7/16	4 1/8
LI-1000-3SC	1000	8.70	2000	34	6	4 3/8	8 1/8	3 7/16	6 3/8

IN STOCK




Provides isolation of power line from ground and is effective in removing hash and line noise for sensitive equipment, e.g. lab instruments, audio equipment, etc.

- 6 FOOT 3 WIRE GROUNDING POWER CORD WITH EUROPEAN "SCHUKO" PLUG
- BUILT-IN U.S. 3 WIRE GROUNDING RECEPTACLE
- SWITCH FOR INPUT VOLTAGE SELECTION

**LEAD WIRES FOR  
PERMANENT WIRING****210/230/250 VOLTS INPUT** → **115 VOLTS OUTPUT****50 → 1000 VA ISOLATION**  
ELECTROSTATIC SHIELD CONNECTED TO CORE

CATALOG NUMBER	MAX.VA (WATTS)	NOMINAL AMPS	HIPOT TEST VOLTS	WEIGHT LBS.	DIMENSIONS				
					H	W	D	MW	MD
LI-50-3L	50	0.44	2000	3	3 1/2	2 7/8	3 7/8	2 1/4	2 1/2
LI-100-3L	100	0.87	2000	4 1/2	3 1/2	2 7/8	4 3/8	2 1/4	3
LI-250-3L	250	2.17	2000	11 1/2	4 5/8	3 7/8	5 1/8	3	4
LI-500-3L	500	4.35	2000	19	6	4 3/8	5 7/8	3 7/16	4 1/8
LI-1000-3L	1000	8.70	2000	34	6	4 3/8	8 1/8	3 7/16	6 3/8

IN STOCK



Provides isolation of power line from ground and is effective in removing hash and line noise for sensitive equipment, e.g. lab instruments, audio equipment, etc.

- FOUR 12 INCH LEAD WIRES USED FOR PERMANENT WIRING
- SWITCH FOR INPUT VOLTAGE SELECTION

NOTE: WHEN USING A TRANSFORMER WITH MORE THAN ONE APPLIANCE AT A TIME, THE TOTAL WATTAGE OF ALL APPLIANCES USED TOGETHER SHOULD NOT EXCEED THE MAX.VA (WATTS) OF THAT TRANSFORMER.

QUALITY ENGINEERED

**TODD SYSTEMS**

INC.

PRECISION BUILT

FAX: (914) 963-3506

50 ASH STREET, YONKERS, NY, 10701 U.S.A.

www.toddsystems.com

(914) 963-3400